

FRANLUBE #38

EJECTOR PIN LUBRICANT

DESCRIPTION: Franlube #38 is a non-pigmented specialty compound developed to withstand extreme temperatures while keeping the ejector pins lubricated.

APPLICATION: Franlube #38 can be applied by brush or grease gun. Normally pins should be lubricated during die assembly. In day-to-day usage the lubricant can be applied while the die is in the machine. A periodic maintenance check of the ejector pins will help determine frequency of application.

BENEFITS: #38 will withstand temperatures in excess of 650°F. The unique blend of lubricating oils and high-pressure additives enables this product to adhere to pins. It will not run off or drip at these temperatures.

ENVIRONMENTAL: Although this product is petroleum based, it is compatible with most waste treatment systems.

PHYSICAL CHARACTERISTICS:

Appearance.....	Blue gel
Odor.....	Mild petroleum
Flash Point.....	>200° F (C.O.C.)
Shelf Life.....	Concentrate: 6-9 months
Toxicity.....	Refer to MSDS before use

SAFETY DATA & HANDLING: Please refer to the MSDS for additional information.

PACKAGING: 1-gallon and 5-gallon Pails

The information contained in this technical bulletin is, to the best of our knowledge, true and accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. This product should be used as per LaFrance recommendations and should not be modified.