

FRANLUBE PL-44 (LV)

WATER-SOLUBLE PLUNGER LUBRICANT

DESCRIPTION: A unique concept in liquid plunger lubricant technology incorporating petroleum oil derivatives. This lubricant is formulated from extreme pressure additives for use on beryllium copper and steel tips. PL-44 (LV) is made up of various compounds to enhance the lubricating characteristics for specific applications. This product does not contain graphite.

APPLICATION: PL-44 (LV) can be diluted with water or used as supplied. The application method preferred is any automatic system that is presently available on the market. However, application by brush method is acceptable.

Maintain consistent quantities of lubricant with each shot. Preventive maintenance of the lubricant applicator and the die cast machine itself will result in the maximum performance possible from this unique dry plunger lubricant.

BENEFITS: This liquid plunger lubricant can be cleaned with warm water and soap. The shot end of the machine stays clean, thus eliminating the use of solvent used in maintenance operations.

ENVIRONMENTAL: This product is non-hazardous.

PHYSICAL CHARACTERISTICS:

Appearance: Off-white Liquid
Odor: Mild
Flash Point: Non-contains water
Viscosity: 2000 cps
Shelf Life: 6 – 9 months
Toxicity: Refer to MSDS Sheet
Weight: 8.0 lbs/gal

SAFETY DATA & HANDLING: Please refer to the MSDS for additional information.

PACKAGING: 5-gallon, 55-gallon and 275-gallon containers.

The information contained in this technical bulletin is, to the best of our knowledge, true and accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. This product should be used as per LaFrance recommendations and should not be modified.